

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



PCT

(43) International Publication Date
4 November 2004 (04.11.2004)

(10) International Publication Number
WO 2004/094319 A1

(51) International Patent Classification⁷: C02F 1/48

(74) Agents: ONSAGERS AS et al.; P.O.Box 6963 St. Olavs
plass, N-0130 Oslo (NO).

(21) International Application Number:

PCT/NO2004/000116

(22) International Filing Date: 23 April 2004 (23.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0309224.4 23 April 2003 (23.04.2003) GB

(71) Applicant (for all designated States except US): EMT RE-
SEARCH ASA [NO/NO]; Kjølnes ring 56, N-3918 Pors-
grunn (NO).

(72) Inventor; and


(75) Inventor/Applicant (for US only): WASKAAS, Magne
[NO/NO]; Sagdalsringen 43, N-3748 Siljan (NO).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: METHOD FOR FLOW IMPROVEMENT AND REDUCTION OF FOULING IN PROCESS EQUIPMENT



(57) Abstract: This invention relates to a method and apparatus for improvement of flow rates and reduction of fouling in process equipment such as for instance heat exchangers (2) where fluids are flowing in single or multiphase. This is obtained by imposing a DC-potential at the walls of the process equipment that exactly opposes the naturally occurring potential due to interaction between the walls of the process equipment and the fluid flowing inside. An improved flow rate will cause that the heat exchanger (2) becomes more efficient, i.e. a lower deposition rate and a higher removal rate of inorganic agents. The fluid may be a pure fluid, colloidal fluid or contain inclusions in the form of particles.

WO 2004/094319 A1